

630 & 1250 Mailbox Material Specification Sheet

MIDDLE VERTICAL BAR: EXTRUDED 6063-T6 ALUMINUM, MILL FINISH
0.44 X 0.72 CROSS SECTION

OUTER VERTICAL BAR: EXTRUDED 6063-T6 ALUMINUM, MILL FINISH
0.72 X 0.25 CROSS SECTION

TOP BAR: EXTRUDED 6061-T6 ALUMINUM, ANODIZED FINISH
0.84 X 0.68 CROSS SECTION

BOTTOM BAR: EXTRUDED 6061-T6 ALUMINUM, ANODIZED FINISH
0.84 X 0.19 CROSS SECTION

BACK, BOTTOM & SIDE PANELS: GALVANNEALED STEEL
24 GAUGE THICKNESS

SINGLE COMPARTMENT DOOR: EXTRUDED 6063-T5 ALUMINUM, ANODIZED FINISH
0.08 NOMINAL THICKNESS
0.25 RIB THICKNESS

DOUBLE COMPARTMENT DOOR: EXTRUDED 6063-T5 ALUMINUM, ANODIZED FINISH
0.13 NOMINAL THICKNESS
0.25 RIB THICKNESS

OUTER TRIM: EXTRUDED 6063-T5 ALUMINUM, ANODIZED FINISH
1.13 X 1.13 CROSS SECTION

NOTES:

1. MATERIAL SPECIFICATIONS SHOWN
ARE APPROVED BY U.S. POSTAL SERVICE
FOR REPLACEMENT PURPOSE ONLY.
2. ALL DIMENSIONS ARE IN INCHES.

PRODUCT SERIES: 630 & 1250 SERIES MAILBOX
MATERIAL SPECIFICATION SHEET

MODEL	VERTICALS	REV	A
SCALE	NONE	LAST REV DATE	11/17/08
DRAWING NUMBER	CS2037	DRAWN BY	NBC
		SHEET	1 OF 1